

Fastgrip™

#14

AVAILABLE IN
ANY COLOR

QUICK
SHIPPING

Ensure superior holding power for OSB and plywood construction with the mechanical galvanized #14 roofing screw. Great pull out resistance is this fastener's strength. Tight sealing EPDM washer and type 17 point.



Fastgrip™

#14



ITEM #	DESCRIPTION	HEAD STYLE	DRILL POINT	PCS/BOX	LB/BOX
141FG	#14 x 1"	5/16 Hex	T-17	2,000	28.6
14112FG	#14 x 1 - 1/2"	5/16 Hex	T-17	1,500	27.8
142FG	#14 x 2"	5/16 Hex	T-17	1,000	23.4
14212FG	#14 x 2 - 1/2"	5/16 Hex	T-17	500	14.2

PULL OUT STRENGTH

SUBSTRATE	PENETRATION	PULL OUT STRENGTH
3/4" Ply	Full	621
1/2" Ply	Full	449
7/16" OSB	Full	209
2 x Yellow Pine	1"	992
2 x Spruce Pine Fir	1"	1,294
2 x Spruce Pine Fir	1 - 1/2"	1,597

SHEAR
2,980
TENSILE
4,492
TORSIONAL
175



PULL OVER STRENGTH

SUBSTRATE	GAUGE	THICKNESS	PULL OVER STRENGTH
AZ55 Galvalume	29	0.014	535
AZ55 Galvalume	26	0.018	743
AZ55 Galvalume	24	0.024	1,052

ALSO AVAILABLE:



TuffGrip™



Fastgrip™
MINI-DRILLER



ProZ™



ProZ™
MINI-DRILLER