









The Fastgrip[™] #10 Hi-Lo MINI-DRILLER[™] has all of the specs that make the Fastgrip[™] #10 Hi-Lo the go-to fastener, but with the added MINI-DRILLER[™] point. The MINI-DRILLER[™] makes easy work of driving through metal panels, while the Hi-Lo thread provides superior pull-out strength in metal to wood applications.













ITEM#	DESCRIPTION	HEAD STYLE	DRILL POINT	PCS/BOX	LB/BOX
101MD	#10 × 1"	1/4 Hex	RP	3,000	26.8
10112MD	#10 × 1 - 1/2"	1/4 Hex	RP	2,500	27.9
102MD	#10 × 2"	1/4 Hex	RP	2,000	27.3
10212MD	#10 × 2 - 1/2"	1/4 Hex	RP	1,500	23.5
103MD	#10 × 3"	1/4 Hex	RP	1,000	19.0

PULL OUT STRENGTH

SUBSTRATE	PENETRATION	PULL OUT STRENGTH	
3/4" Ply	Full	525	
1/2" Ply	Full	280	
7/16" OSB	Full	217	
2 x Yellow Pine	1"	850	
2 x Spruce Pine Fir	1"	787	
2 x Spruce Pine Fir	1 - 1/2"	1,285	

SHEAR				
1,750				
TENSILE				
2,486				
TORSIONAL				
80				



PULL OVER STRENGTH

SUBSTRATE	GAUGE	THICKNESS	PULL OVER STRENGTH
AZ55 Galvalume	29	0.014	398
AZ55 Galvalume	26	0.018	667
AZ55 Galvalume	24	0.024	767

ALSO AVAILABLE:













