

Pancake Head

SELF-DRILLING

#10



Choose the pancake head to achieve a low-profile, flush finish. Zinc plated with #3 self-drilling point for metal to metal applications. In-stock colors ship quickly or match to your roof color.



Pancake Head

SELF-DRILLING

#10



ITEM #	DESCRIPTION	HEAD STYLE	DRILL POINT	PCS/BOX	LB/BOX
101PHSD	#10 x 1"	Phillips/Square	#2	5,000	34.9
10112PHSD	#10 x 1 - 1/2"	Phillips/Square	#2	2,500	24.1

PULL OUT STRENGTH

SUBSTRATE	PENETRATION	PULL OUT STRENGTH	SHEAR
3/4" Ply	Full	387	1,620
1/2" Ply	Full	274	
7/16" OSB	Full	201	TENSILE
2 x Yellow Pine	1"	490	1,900
2 x Spruce Pine Fir	1"	434	TORSIONAL
2 x Spruce Pine Fir	1 - 1/2"	646	77



PULL OVER STRENGTH

SUBSTRATE	GAUGE	THICKNESS	PULL OVER STRENGTH
AZ55 Galvalume	29	0.014	425
AZ55 Galvalume	26	0.018	717
AZ55 Galvalume	24	0.024	1,120

ALSO AVAILABLE:



Pancake Head

T-17



Pancake Head

300 Series
Stainless Steel



Pancake Head

Low Profile