

Pancake Head

ZINC PLATED

#10



Choose the zinc plated pancake head to achieve a low-profile, flush finish. T-17 drill points available in multiple lengths. In-stock colors ship quickly or match to your roof color.



Pancake Head

ZINC PLATED

#10



ITEM #	DESCRIPTION	HEAD STYLE	DRILL POINT	PCS/BOX	LB/BOX
101PH17	#10 x 1"	Phillips/Square	T-17	5,000	33.9
10112PH17	#10 x 1 - 1/2"	Phillips/Square	T-17	2,500	23.6
102PH17	#10 x 2"	Phillips/Square	T-17	2,000	23.1

PULL OUT STRENGTH

SUBSTRATE	PENETRATION	PULL OUT STRENGTH
3/4" Ply	Full	464
1/2" Ply	Full	306
7/16" OSB	Full	228
2 x Yellow Pine	1"	704
2 x Spruce Pine Fir	1"	653
2 x Spruce Pine Fir	1 - 1/2"	1,102

SHEAR
1,500
TENSILE
1,930
TORSIONAL
70



PULL OVER STRENGTH

SUBSTRATE	GAUGE	THICKNESS	PULL OVER STRENGTH
AZ55 Galvalume	29	0.014	467
AZ55 Galvalume	26	0.018	626
AZ55 Galvalume	24	0.024	992

ALSO AVAILABLE:



Pancake Head
Self-Drilling



Pancake Head
300 Series
Stainless Steel



Pancake Head
Low Profile