

ProZ™ SD

#3
Drill Point



#12

AVAILABLE IN
ANY COLOR

QUICK
SHIPPING

Ensuring a weather tight seal for metal to metal installations is easy with ProZ™ SD. The design of the washer head reduces overdriving and can never red rust with the zinc aluminum alloy cap. ProZ™ SD provides a strong cap that withstands the toughest installation conditions and is compatible with all panel finishes. Self-drilling #5 and stitch drill points are also available.





ITEM #	DESCRIPTION	HEAD STYLE	DRILL POINT	PCS/BOX	LB/BOX
121PZSD	#12 - 14 x 1"	5/16 Hex	#3	2,500	28.1
12114PZSD	#12 - 14 x 1 - 1/4"	5/16 Hex	#3	2,500	27.9
12112PZSD	#12 - 14 x 1 - 1/2"	5/16 Hex	#3	2,000	27.5
122PZSD	#12 - 14 x 2"	5/16 Hex	#3	2,000	26.1
123PZSD	#12 - 14 x 3"	5/16 Hex	#3	500	19.7

PULL OUT STRENGTH

SUBSTRATE	PULL OUT STRENGTH
12 ga HRS	1,223
14 ga HRS	723
16 ga HRS	587
18 ga HRS	418
20 ga HRS	302

SHEAR
2,800
TENSILE
4,500
TORSIONAL
129



PULL OVER STRENGTH

SUBSTRATE	GAUGE	THICKNESS	PULL OVER STRENGTH
AZ55 Galvalume	29	0.014	577
AZ55 Galvalume	26	0.018	855
AZ55 Galvalume	24	0.024	1,213
AZ55 Galvalume	22	0.030	1,254

ALSO AVAILABLE:

