

ProZ™ SD



Ensuring a weather tight seal for metal to metal installations is easy with ProZ™ SD. The design of the washer head reduces overdriving and can never red rust with the zinc aluminum alloy cap. ProZ™ SD provides a strong cap that withstands the toughest installation conditions and is compatible with all panel finishes. Self-drilling #3 and stitch drill points are also available.





ITEM #	DESCRIPTION	HEAD STYLE	DRILL POINT	PCS/BOX	LB/BOX
1224114PZSD	#12 - 24 x 1 - 1/4"	5/16 Hex	#5	2,500	43.0

PULL OUT STRENGTH

SUBSTRATE	PULL OUT STRENGTH
12 ga HRS	806
14 ga HRS	497
16 ga HRS	410
18 ga HRS	268
20 ga HRS	196

SHEAR
2,760
TENSILE
3,246
TORSIONAL
100



PULL OVER STRENGTH

SUBSTRATE	GAUGE	THICKNESS	PULL OVER STRENGTH
AZ55 Galvalume	29	0.014	561
AZ55 Galvalume	26	0.018	710
AZ55 Galvalume	24	0.024	1,009
AZ55 Galvalume	22	0.030	924

ALSO AVAILABLE:



ProZ SD
#3



Metalgrip™
#3



Metalgrip™
#5



ProZ
MINI-DRILLER™