

# Pancake Head

ZINC PLATED

#10



Choose the zinc plated pancake head to achieve a low-profile, flush finish. T-17 drill points available in multiple lengths. In-stock colors ship quickly or match to your roof color.



# Pancake Head

ZINC PLATED

#10



ITEM #	DESCRIPTION	HEAD STYLE	DRILL POINT	PCS/BOX	LB/BOX
101PH17	#10 x 1"	Phillips/Square	T-17	5,000	33.9
10112PH17	#10 x 1 - 1/2"	Phillips/Square	T-17	2,500	23.6
102PH17	#10 x 2"	Phillips/Square	T-17	2,000	23.1

## PULL OUT STRENGTH

SUBSTRATE	PENETRATION	PULL OUT STRENGTH
3/4" Ply	Full	464
1/2" Ply	Full	306
7/16" OSB	Full	228
2 x Yellow Pine	1"	704
2 x Spruce Pine Fir	1"	653
2 x Spruce Pine Fir	1 - 1/2"	1,102

SHEAR
1,500
TENSILE
1,930
TORSIONAL
70



## PULL OVER STRENGTH

SUBSTRATE	GAUGE	THICKNESS	PULL OVER STRENGTH
AZ55 Galvalume	29	0.014	467
AZ55 Galvalume	26	0.018	626
AZ55 Galvalume	24	0.024	992

## ALSO AVAILABLE:



**Pancake Head**  
Self-Drilling



**Pancake Head**  
300 Series  
Stainless Steel



**Pancake Head**  
Low Profile