

# Pancake Head

LOW PROFILE

#10



This ultra-thin pancake head fastener is designed to fasten flush and lay flat without dimpling or showing through the panel. Available in three sizes with SP drill point and #2 square, low profile head style.



# Pancake Head

LOW PROFILE

#10



ITEM #	DESCRIPTION	HEAD STYLE	DRILL POINT	PCS/BOX	LB/BOX
101PHLP	#10 x 1"	#2 Square	SP	5,000	28.7
1012PHLP	#10 x 1 - 1/2"	#2 Square	SP	2,500	26.8
102PHLP	#10 x 2"	#2 Square	SP	2,000	23.2

## PULL OUT STRENGTH

SUBSTRATE	PENETRATION	PULL OUT STRENGTH
3/4" Ply	Full	484
1/2" Ply	Full	280
7/16" OSB	Full	196
2 x Yellow Pine	1"	677
2 x Spruce Pine Fir	1"	814
2 x Spruce Pine Fir	1 - 1/2"	909

<b>SHEAR</b>
1,750
<b>TENSILE</b>
2,544
<b>TORSIONAL</b>
83



## PULL OVER STRENGTH

SUBSTRATE	GAUGE	THICKNESS	PULL OVER STRENGTH
AZ55 Galvalume	29	0.014	465
AZ55 Galvalume	26	0.018	649
AZ55 Galvalume	24	0.024	978

## ALSO AVAILABLE:



**Pancake Head**

T-17



**Pancake Head**

Self-Drilling



**Pancake Head**

300 Series  
Stainless Steel