


Pancake Head

LOW PROFILE

#10



This ultra-thin pancake head fastener is designed to fasten flush and lay flat without dimpling or showing through the panel. Available in three sizes with SP drill point and #2 square, low profile head style.



Pancake Head

LOW PROFILE

#10



QUICK SHIPPING

ITEM #	DESCRIPTION	HEAD STYLE	DRILL POINT	PCS/BOX	LB/BOX
101PHLP	#10 x 1"	#2 Square	SP	5,000	28.7
1012PHLP	#10 x 1 - 1/2"	#2 Square	SP	2,500	26.8
102PHLP	#10 x 2"	#2 Square	SP	2,000	23.2
10212PHLP	#10 x 2 - 1/2"	#2 Square	SP	1,500	21.0

PULL OUT STRENGTH

SUBSTRATE	PENETRATION	PULL OUT STRENGTH
3/4" Ply	Full	484
1/2" Ply	Full	280
7/16" OSB	Full	196
2 x Yellow Pine	1"	677
2 x Spruce Pine Fir	1"	814
2 x Spruce Pine Fir	1 - 1/2"	909

SHEAR
1,750
TENSILE
2,544
TORSIONAL
83



PULL OVER STRENGTH

SUBSTRATE	GAUGE	THICKNESS	PULL OVER STRENGTH
AZ55 Galvalume	29	0.014	465
AZ55 Galvalume	26	0.018	649
AZ55 Galvalume	24	0.024	978

ALSO AVAILABLE:



Pancake Head

T-17



Pancake Head

Self-Drilling



Pancake Head

300 Series
Stainless Steel